GUHRING



Induction Shrink Fit Systems

Work easily, quickly and efficiently ...



The advantages of shrink fit technology:

Perfect 360° tool clamping provides extreme clamping force and rigidity

High repeatability, hence reduced operating errors

Minimal imbalance thanks to rotational symmetry

Excellent concentricity

Reduced components, therefore lower costs for purchasing, storage and administration

You benefit trom:

High economical efficiency

Longer tool life

Considerable time saving

... with each application!



Safe shrink fitting

The minimal heating of the shrink fit chuck ensures maximum operating safety on the one hand, on the other the controlled heating ensures the long life of the shrink fit chuck.



The control panel

The clear control panel with display makes the operation of the GSS 2000 very user-friendly.

Simple operation

The movement of the spindle and its heating is a single handed operation.

Tool clamping cannot be simpler and quicker!

Quick cooling

The water-cooled cooling elements cool down the shrink fit chuck quickly and safely. The shrink fit chuck remains clean and dry, so that it can be applied again without drying and without rusting. Hot spots remain safely screened during the cooling process in order to prevent burns.

Efficient operation

The turntable allows simultaneous preparation, heating and cooling of the shrink fit chucks. Subsequently, there is no waiting time, tool clamping is seamless and with maximum efficiency.

All under control

Practical locations and compartments provide room for accessories such as stop discs or gloves in close proximity to the equipment. Thus all the necessary components are always at hand.

Comfort Plus

GSS 2000

With turntable.

The GSS 2000 Comfort Plus is the complete solution for simple, quick and secure tool clamping in the shrink fit chuck.





Put an end to complex tool clamping and adjustment.

With GSS 2000 you can clamp your tools easily, quickly and securely.

Benefit from the advantages of GSS 2000:

- >high-performance spindle, hence quick change time
- >overheating protection for holder
- > automatic mode possible (equipment automatically selects the correct heating program)
- >error detection choosing wrong chuck/program
- >heating programs for standard/reinforced and very small holder/shrink fit extensions
- >maximum rigidity
- >highest cutting rates



ECO OLAS Single station alternative

Full performance

The GSS 2000 Eco Plus is a single-position system that provides the full induction and cooling performance of a professional system at a reasonable cost.



Basic

For new starters without cooling

<u>GSS</u>

Reduced to the essentials

For newcomers to the shrink fit technology the GSS 2000 offers all necessary equipment features for clamping or unclamping tools, but dispenses with the cooling.





1) Swivel tray

The practical swivel tray can be directly located within the GSS 2000 to accommodate the most important accessories.

ACCESSOIRIES

2) Trolley

The sturdy trolley provides the GSS 2000 with secure positioning and location for the SpeedCooler. The spacious drawer of the trolley provides additional room for further accessories. As a result, everything is in its place.





3 Pliers

For the safe handling of hot tools.

THERMO SECURE

GOLD 3000

Perfect combination:

GSS 2000 + TSG 3000



perfect concentricity
highest balance
maximum operational safety



Enquiry for GSS 2000

Comfort Plus

☐ GSS 2000 Comfort-Plus

4742 10.000



Basic unit and accessories

Test our Comfort Plus for 4 weeks free of charge

		System trolley 4748 1.000	•			
		Pliers 4749 1.000				
		Swivel trays 4763 1.000				
			appropriate	holders		
	HSK holders		SK holders			
		HSK 32 4745 32.000				
		HSK 40 4745 40.000			SK 40 4744 40.000	
		HSK 50 4745 50.000		٠	SK 50 4744 50.000	
		HSK 63 4745 63.000				
		HSK 80 4745 80.000				
		HSK 100 4745 100.000				
Are tool diameter	s 3-5 n	nm applied?				
Company:				Company stamp) :	
Telephone/fax:						
Contact name:				Signature:		

Enquiry for GSS 2000 Eco plus / Basic



Basic unit and accessories

	GSS 2000 Eco P 4752 10.000	lus		GSS 2000 Basic 4730 10.000
	System trolley 4748 1.000			
0	Pliers 4749 1.000			
	Swivel trays 4763 1.000			
	appro	priate holders		
HSK	holders		SK ho	Iders
	HSK 32 4761 32.000			
	HSK 40 4761 40.000			SK 40 4762 40.000
	HSK 50 4761 50.000			SK 50 4762 50.000
	HSK 63 4761 63.000			
	HSK 80 4761 80.000			
	HSK 100 4761 100.000			
Are tool diameters 3-5 n	nm applied?			
Company:	Company s	stamp:		
Telephone/fax:				
Contact name:		Signature:		





SPECIAL TOOLING SOLUTIONS

COUNTERSINKING/ DE-BURRING MODULAR TOOLING SYSTEMS

TOOL RESTORATION SERVICE

GUHRING

Gühring oHG

Postfach 100247 • 72423 Albstadt Herderstraße 50-54 • 72458 Albstadt

Tel. +49 74 31 17-0 Fax +49 74 31 17-21279 info@guehring.de www.guehring.de

Your contact: Mathias Hirt

Product Manager Shrink Fit Systems

Tel. +49 74 31 17-25 028 Fax +49 74 31 17-25 666 mathias.hirt@guehring.de

